


| Date | SYM | REVISION RECORD | AUTH | DR. | CK. |
|---------|-----|--|------|------|-----|
| 4/15/06 | A | ADDED "ROHS COMPLIANT" UPDATED MATERIAL NOTE | T.B. | B.S. | |
| | | | | | |
| | | | | | |
| | | | | | |

NOTES:

1. MATERIAL:

- HOUSING : BLACK POLYPROPYLENE, PP-1040
- FLAMMABILITY RATING -UL94-HB, UL FILE NO. E216959
- TEMPERATURE RANGE: -10°C to +100°C
- RIVETS: BRASS, NICKLE PLTD.
- SPRING: SPRING STEEL, NICKLE PLTD.
- WIRE: 26AWG, UL1007, CSA, TR64
- CONTACT RESISTANCE: UNDER 50mΩ FOR +/- CONTACTS PER EIA-540J000
- ROHS COMPLIANT

| | | | |
|--------------------------------|--|-----------------|----------------------------|
| Tolerance (Except as noted) |  Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735 | Scale | Drawn By B.S. |
| | | | Approved By T.B. |
| decimal ±.5 (.020) | Title EIGHT "AAA" CELL HOLDER | | |
| Fractional ± .8 (.030) | | Date 4/15/06 | Drawing Number BH28AAAW |
| Angular ± 3° | | | |